



**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)




IB04/52288



INVESTOR IN PEOPLE

**The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ**



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Qthame

Dated 2 September 2004



1/77

Request for grant of a patent

(See notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP10 8QQ

1. Your reference	PHGB 030201 GBP		
	10NOV03 E850673-1 D02879		
	P01/7700 0.00 0326095.7		
2. Patent application number (The Patent Office will fill in this part)	0326095.7		
3. Full name, address and postcode of the or of each applicant (<u>underline all surnames</u>)	KONINKLIJKE PHILIPS ELECTRONICS N.V. GROENEWOUDSEWEG 1 5621 BA EINDHOVEN THE NETHERLANDS 07419294001 ✓		
Patents ADP Number (if you know it)			
If the applicant is a corporate body, give the country/state of its incorporation	THE NETHERLANDS		
4. Title of the invention	GPS RECEIVER AND RELATED METHOD AND APPARATUS		
5. Name of your agent (if you have one)			
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	Philips Intellectual Property & Standards Cross Oak Lane Redhill Surrey RH1 5HA		
Patents ADP number (if you know it)	08359655001 ✓		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority Application number	Date of filing
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day/month/year)	
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer "Yes" if:	YES		
a) any applicant named in part 3 is not an inventor, or			
b) there is an inventor who is not named as an applicant, or			
c) any named applicant is a corporate body.			
See note (d))			

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document.

Continuation sheets of this form

Description

6

Claims(s)

3

Abstract

1

Drawings

1

ONLY *TS*

10. If you are also filing any of the following, state how many against each item:

Priority Documents

Translations of priority documents

Statement of inventorship and right

to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and

search (*Patents Form 9/77*)

Request for substantive examination

(*Patents Form 10/77*)

Any other documents

(*Please specify*)

11. I/We request the grant of a patent on the basis of this application.

Signature

Stam send

Date

7/11/2003

12. Name and daytime telephone number of person to contact in the United Kingdom 01293 81 5339 S TOWNSEND

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered "Yes" Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

DESCRIPTION

GPS RECEIVER AND RELATED METHOD AND APPARATUS

5 The present invention relates to a GPS receiver comprising a GPS antenna and a GPS RF front-end including an analogue to digital converter for sampling received GPS signals; and a processor for outputting the GPS signal samples.

10 The present invention further relates to a corresponding method of providing a position fix comprising the steps of receiving from a GPS receiver GPS signal samples and processing the GPS signal samples to determine a position fix; and to a computer program, computer-readable storage medium and apparatus for the same.

15 Article "Real-time software radio architectures for GPS receivers" by Akos et al. (GPS World, July 2001) discloses "software GPS" in which much GPS signal processing is accomplished by means of a programmable micro-processor or digital signal processor as opposed to analogue or discrete hardwired components. As illustrated in figure 2 of this article, a simplified GPS
20 receiver is provided consisting of a GPS antenna and GPS RF front-end for GPS signal pre-processing (including filtering, amplification and frequency down-conversion) and analogue to digital conversion. GPS signal samples outputted from the GPS receiver are then fed in to a modern PC or laptop running appropriate GPS signal processing software for processing the GPS
25 signals to determine a position fix. The authors of this article have contemplated the GPS receiver to be a "plug-in" module, i.e. a "dongle" type device, which because of its simple architecture could be manufactured cheaply, thereby facilitating widespread adoption. And, of course, the GPS signal processing software which resides on the PC is inherently cheap to
30 replicate.

 Whatever specific GPS receiver architecture and GPS signal processing software configuration are adopted, it would be of course be

expected that the output of the GPS receiver is compatible with the GPS signal processing software. In other words, since the attributes of the interface between the GPS receiver and GPS signal processing software are known, one or both would be designed with the other in mind. For example, the GPS
5 signal processing software might have been configured to handle GPS signal samples of format, rate and resolution outputted by the GPS receiver.

In accordance with the present invention, there is provided a GPS receiver of the aforementioned type in which the processor outputs (especially
10 to an external device) the GPS signal samples together with ancillary information either directly or indirectly describing characteristics of the GPS signal samples and / or the GPS signals contained therein.

Also provided in accordance with the present invention is a method of providing a position fix comprising the steps of: receiving from a GPS receiver
15 GPS signal samples together with ancillary information describing characteristics of the GPS signal samples and / or the GPS signals contained therein and processing the GPS signal samples using the ancillary information to determine a position fix; and a computer program, computer-readable storage medium and apparatus for the same.

20 The inventors have realised that future software GPS systems may not necessarily have their GPS receivers (i.e. the GPS antenna and GPS RF front-end portion) and their GPS signal processing software designed with each other in mind. The present invention provides a mechanism by which GPS signal processing software receiving the ancillary information can establish
25 and then adapt to the characteristics of a particular GPS receiver's output. This enables particular GPS signal processing software to process signals outputted from a variety of GPS receivers, and which may even have been designed and / or manufactured by different companies.

30 The present invention will now be described, by way of example only, with reference to the accompanying figure which shows, schematically, a

laptop PC connected to a GPS receiver, both operating in accordance with the present invention.

Referring to the accompanying figure, the laptop PC is connected via a
5 USB PC port and corresponding cable to the GPS receiver 10 which consists
of a GPS RF front-end Rx and a GPS antenna. Whilst the GPS receiver could
have been a "dongle" type device thereby omitting the cable, the cable
facilitates positioning of the GPS receiver (including the antenna) in a
prominent position, thereby increasing the chances of acquiring GPS signals.
10 For example, one might place the GPS receiver near a window if operating in
doors.

When operative, the GPS receiver receives NAVSTAR SPS GPS
signals through its antenna and pre-process them, typically by passive
bandpass filtering in order to minimise out-of-band RF interference,
15 preamplification, down conversion to an intermediate frequency (IF) and
analogue to digital conversion. The resultant GPS signal samples contain the
IF signal which remains modulated, still containing all the information from the
available satellites.

In accordance with the present invention, the GPS signal samples are
20 outputted from the GPS receiver via the USB link into PC memory (not shown)
with ancillary information describing characteristics of the GPS signal samples
and / or the GPS signals contained therein.

Using laptop PC based GPS signal processing software and the
ancillary information, the GPS signal samples are then processed so that GPS
25 signals may be acquired for the purpose of deriving pseudorange information from
which the position of the PC can be determined using conventional navigation
algorithms. Such GPS signal acquisition and pseudorange processing is well
known, for example, see GPS Principles and Applications (Editor, Kaplan)
ISBN 0-89006-793-7 Artech House.

The ancillary information may include the following:

Information relating to the GPS receiver itself:

- 5 ▪ type and / or identity of the GPS receiver. If the GPS signal processing software can access a database mapping the type and / or identity of a GPS receiver to characteristics of GPS signal samples outputted that particular GPS receiver and / or the GPS signals that particular GPS receiver is used to receive, then the type and / or identity of the GPS receiver can be indirectly used by such
- 10 GPS signal processing software to process the GPS signal samples.

Information relating to the GPS signal received by the GPS receiver:

- 15 ▪ type and / or identity of the received GPS signal. A particular GPS receiver may be designed to receive different GPS signals and / or operate in one or a plurality of operating modes as, for example, directly selected by a user using user input means of the GPS receiver.
- received GPS signal(s) format
- received GPS signal(s) centre frequency
- 20 ▪ received GPS signal(s) bandwidth

Information relating to the GPS samples outputted by the GPS receiver:

- 25 ▪ outputted GPS signal carrier frequency. The received GPS signal will typically be down converted to an intermediate frequency (IF) by the GPS receiver.
- outputted GPS signal bandwidth. This ought to corresponding to filtering done by the GPS receiver.
- outputted GPS signal sample format
- outputted GPS signal sample rate
- 30 ▪ outputted GPS signal sample resolution

- image sign; that is, whether an increase in the frequency of the received GPS signal results in either an increase or decrease in the outputted GPS signal sample carrier frequency
- oscillator type and / or oscillator stability parameters; for example, whether the GPS receiver's oscillator has temperature compensation and if it does, accuracy parameters, and if not, error parameters.
- antenna type; for example, indicating the effective beam pattern.

10 Where appropriate, the ancillary information may also include information relating to the accuracy of any of the above.

It is likely there will be a requirement for at least some initialisation between the laptop PC and the GPS receiver, for example, triggered by the laptop's operating system detecting the presence of the GPS receiver. This
15 may include an exchange of ancillary information prior to streaming GPS signal samples in to the laptop PC so enable the GPS software to correctly receive the data and to allow the GPS signal processing software to select a preferred configuration.

Whilst the present invention has been illustrated in the context of a
20 laptop PC, it is of course equally applicable to other apparatus able to support GPS signal processing software and to which a GPS receiver according to the present invention can be connected. For example, the invention may be employed with mobile devices such as PDAs and telephone; or generally stationary objects such as a TVs or TV set-top boxes.

25 Also, whilst the connection between the GPS receiver and the GPS signal processing software is entirely wired in the above example, it could conceivable involve a wireless link.

Furthermore, the GPS receiver shown in the accompanying figure may be provided with user input means with which a user may directly select one of
30 a plurality of operating modes. For example, the user may change something relating to the GPS signal received by the GPS receiver such as at what centre frequency the GPS receiver is expecting to receive GPS signals should there

be more than one possible frequency for target signals. In an alternative example, the user may change something relating to the GPS samples outputted by the GPS receiver such as at what sample rate or resolution the GPS signal samples are outputted.

5 As stated above, information relating to the GPS receiver's oscillator may be outputted by the GPS receiver to assist the laptop PC based GPS signal processing software. Oscillators generally have a stated operating frequency range corresponding to manufacturing tolerances, but it likely that the actual operating frequency which falls within this range is very stable. If
10 such an oscillator in the GPS receiver is individually calibrated, this calibration information or a derivative thereof (e.g. the subsequent change in GPS signal sample output frequency) can be provided to the GPS signal processing software. The GPS signal processing software can actually perform the calibration itself by analysing the GPS receivers measurement of the
15 frequency of received GPS signals. Once a position fix has been determined, the frequency of the received GPS signals can be determined authoritatively and hence the GPS receivers measurement error quantified. This error may then be uploaded to the GPS receiver and stored in say a flash memory so that subsequently, the GPS receiver can output this calibration information to
20 assist GPS signal processing software performing a position fix.

Finally, whilst the invention has been described in the context of NAVSTAR GPS, the all weather, spaced based navigation system developed and currently operated by the US Department of Defense, it will be appreciated that the invention is equally applicable to other global positioning systems
25 including GLONASS and Galileo and hybrids thereof.

CLAIMS

1. A GPS receiver comprising a GPS antenna and a GPS RF front-end including an analogue to digital converter for sampling received GPS signals;
5 and a processor for outputting the GPS signal samples together with ancillary information either directly or indirectly describing characteristics of the GPS signal samples and / or the GPS signals contained therein.
2. A GPS receiver according to claim 1 wherein the GPS signal samples
10 and ancillary information are outputted to an external device.
3. A GPS receiver according to claim 1 wherein the ancillary information includes information relating to the type or identity of the GPS receiver.
- 15 4. A GPS receiver according to claim 1 wherein the ancillary information includes information relating to the GPS signal received by the GPS receiver
5. A GPS receiver according to claim 4 wherein the ancillary information includes either the type or identity of the received GPS signal, or the received
20 GPS signal(s) format, centre frequency or bandwidth.
6. A GPS receiver according to claim 1 wherein the ancillary information includes information relating to the GPS samples outputted by the GPS receiver.
- 25 7. A GPS receiver according to claim 6 wherein the ancillary information includes either the outputted GPS signal carrier frequency or bandwidth, the GPS signal sample format, rate or resolution, the image sign, the oscillator type or oscillator stability parameters, or the antenna type.

8. A GPS receiver according to claim 1 further comprising user input means with which the user is able to directly select one of a plurality of operating modes of the GPS receiver.

5 9. A method of providing a position fix comprising the steps of:

- receiving from a GPS receiver GPS signal samples together with ancillary information describing characteristics of the GPS signal samples and / or the GPS signals contained therein; and
 - processing the GPS signal samples using the ancillary information to
- 10 determine a position fix.

10. A method according to claim 9 wherein the GPS signal is a spread spectrum signal; and wherein the ancillary information is used to assist despread of the GPS spread spectrum signal.

15

11. A method according to claim 9 wherein the GPS signal samples and ancillary information are received from an external device.

12. A method according to claim 9 wherein the ancillary information
20 includes information relating to the type or identity of the GPS receiver.

13. A method according to claim 9 wherein the ancillary information includes information relating to the GPS signal received by the GPS receiver.

25 14. A method according to claim 13 wherein the ancillary information includes either the type or identity of the received GPS signal, or the received GPS signal(s) format, centre frequency or bandwidth.

15. A method according to claim 9 wherein the ancillary information
30 includes information relating to the GPS samples outputted by the GPS receiver.


16. A method according to claim 15 wherein the ancillary information includes either the outputted GPS signal carrier frequency or bandwidth, the GPS signal sample format, rate or resolution, the image sign, the oscillator
5 type or oscillator stability parameters, or the antenna type.
17. A computer program comprising instructions for performing a method according to any of claims 9 to 16.
- 10 18. A computer-readable storage medium having recorded thereon data containing instructions for performing a method according to any of claims 9 to 16.
- 15 19. Apparatus configured to perform a method according to any of claims 9 to 16.
20. Apparatus according to claim 19 configured to connect to a GPS receiver of the type claimed in any of claims 1 to 8.

ABSTRACT**GPS RECEIVER AND RELATED METHOD AND APPARATUS**

5 A GPS receiver (10) is disclosed comprising a GPS antenna and a GPS
RF front-end including an analogue to digital converter for sampling received
GPS signals; and a processor for outputting, including to an external device,
the GPS signal samples together with ancillary information either directly or
indirectly describing characteristics of the GPS signal samples and / or the
10 GPS signals contained therein.

Also disclosed is a corresponding method of providing a position fix and
a computer program, computer-readable storage medium and apparatus for
the same.

41



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.